

SAFETY DATA SHEET - SC110 HARDENER

Section 1: Identification

Trade Name: Contact Information:

Emergency Contact: Email Address: Website: Recommended Use:

Chemical Family:

SC110 Epoxy King, LLC 2306 Apollo Cir., Carrollton, TX 75006 (877) 701-0744 scott@epoxyking.com https://epoxyking.com UV-Stabilized, Marine-grade clear-coat epoxy coating/primer for use on all indoor/outdoor/industrial and marine surfaces. 2-Part Clear Epoxy

Section 2: Hazard(s) Identification

Hazard Classification: Signal Word: Hazard Statement(s):	Skin Irritant-Category 2 Warning H317 Prolonged exposure may cause an allergic skin reaction	
Pictogram:		
Precautionary Statements:	 P101: If medical advice is needed, have product container or label at hand P102: Keep out of reach of children P103: Read label before use P261: Avoid breathing dust/fume/gas/mist/vapors/spray P280: Wear Protective gloves/protective clothing/eye and face protection P333+P313: If skin irritation/rash occurs, get medical attention P501: Dispose of contents/container in accordance with local/regional/national and intl regulations 	
NFPA Rating:	Health: 1 Flammability: 1 Instability: 0 Specific Hazard: N/A	
HIMS ® Rating:	Health: 1 Health: 1 Flammability: 1 Physical Hazard: 0 Personal Protection Index: C	

Section 3: Composition/Information on Ingredients

Chemical Name/Family: Common Names/Synonyms:	Epoxy Epoxy Resin, Epoxy Coating, Novolac Epoxy, Two-part Epoxy	
CAS Numbers and other Identifiers:		
Hardener:	Modified Cycloaliphatic Amine: CAS# 2855-13-2 Mixture >90%	
	Trade Secret <10%	
	OSHA SACGIH (PEL/STEL) NE (TWA/STEL) NE	
Trade Secret Claim:	Please note that the exact concentration of each chemical contained in the product has been withheld as the exact formula needs to remain a trade secret.	

Section 4: First Aid Measures

Description of first-aid measures for specific exposure:	
For Ingestion:	Call physician immediately. Give generous amounts of water if conscious. Do not induce vomiting.
For Skin Exposure:	Promptly wash with mild soap and water.
For Inhalation:	Remove to fresh air. Give oxygen if breathing is difficult.
For Eye Exposure:	Immediately flush eyes with water for 15 minutes. Call physician.
Description of Overexposure Symptoms and Effects:	Overexposure to this material can cause chemical burns to the skin and eyes and inhalation of vapors can cause severe respiratory irritation. Can cause allergic skin and respiratory reactions. Can have effects on the nervous system evidenced by central nervous system depression, tremors, paralysis, diarrhea and vasodilation. May also cause headache, nausea and dizziness.
Medical Conditions Aggravated by Exposure:	Allergy, eczema or skin conditions.
Additional Information:	Promptly remove wet contaminated non-imperious clothing, wash before reuse. Destroy contaminated leather and absorbent shoes.

Section 5: Fire-Fighting Measures

Flash Point:	>200°F (93°C)
Flash Point Method Used:	Closed cup
Fire Fighting Extinguishing Media:	Carbon Dioxide, foam, dry chemical
Fire Fighting Equipment:	Use a self-contained breathing apparatus
Fire and Explosion Hazards:	Decomposition and combustion products may be toxic.

Section 6: Accidental Release Measures

Steps to be taken if material
is spilled:

Absorb into sand or other absorbent material. Shovel into closeable container and dispose of in professional manner.

Section 7: HandIng and Storage

Handling precautions:

Storage Information:

Do not get in eyes, on skin, on clothing. Do not breathe vapor, mist or spray. Use only with adequate ventilation. Individuals should wash thoroughly after handling. For industrial use only. Keep away from heat, sparks and open flame. Ground and bond metal containers for liquid transfer to avoid static sparks. Store at temperatures between 2°C and 40°C in tightly closed containers in dry area to prevent moisture and carbon dioxide contamination.

Section 8: Exposure Controls/Personal Protection

OSHA PELs:	N/A
ACGIH TLVs:	N/A
Personal Protective Equipment:	Wear protective equipment to prevent exposure and personal contact
Skin Protection:	Impervious gloves
Respiratory Protection:	Organic chemical cartridge respirator if needed in non-vented area
Eye Protection:	Splash-proof chemical goggles
Engineering Controls:	Good general mechanical ventilation and local exhaust

Section 9: Physical and Chemical Properties

Appearance:	Clear
Odor:	Slight ammonia odor
Physical State:	Liquid
Solubility in Water (% by weight):	Negligible
Melting Point:	<0° F (-18° C)
Density:	1.03
pH:	ca 8

Section 10: Stability and Reactivity

Reactivity:	Non Reactive	
Stability:	Stable	
Incompatible Materials:	Strong acids, oxidizers and bases	
Hazardous Decomposition Product Carbon Monoxide, Carbon Dioxide, Phenolic Nitrogen Oxides and Compounds		
Hazardous Polymerization:	Do not heat in bulk as dangerous decomposition may occur, liberating toxic fumes.	

Section 11: Toxicological Information

Acute Oral Effects (Ingestion):	<u>Hardener</u> - LD ₅₀ (rabbits): 3000 mg/kg	
Sensitization:	Can cause skin and respiratory sensitization	
Skin Irritation:	Irritant	
Eye Irritation:	Irritant	

Section 12: Ecological Information

A	dditional Information:	Amines, in general, may be toxic to aquatic organisms.	Epoxies are only slightly soluble in water.
Α	quatic Toxicity:	No further relevant information available	
P	ersistence and Degradability:	No further relevant information available	
В	ocumulative Potential:	No further relevant information available	
N	lobility in Soil:	No further relevant information available	

Section 13: Disposal Considerations

Waste Disposal Method: Recommendations: Dispose in accordance with international, federal (US), state (US) and local regulations Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Section 14: Transport Information

DOT, ADR, AND IMDG, IATA: Hazard Class under: DOT, ADR, AND IMDG, IATA: Marine Pollutant: Notes:

Non-hazardous for transport Non-hazardous for transport No Not Regulated under DOT, ADR, AND, IMDG, IATA

Section 15: Regulatory Information

Occupational Safety and Health Act (OSHA): This Material Safety Data Sheet (MSDS) has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200(g). This product is considered to be a hazardous chemical under that standard.

Resource Conservation and Recovery Act (RCRA): Not a hazardous waste under RCRA (40 CFR 261).

Toxic Substances Control Act (TSCA): All ingredients are on the TSCA inventory and are exempt as per 40CFR723.50 Low Volume Exemption(LVE) and Low Environmental Release and Low Human Exposure Exemption (LOREX).

SARA Title III: Section 304 - CERCLA: Not listed.

SARA Title III: Section 313 Toxic Chemical List (TCL): This product does not contain a toxic chemical for routine annual "Toxic Chemical Release Reporting" under Sec. 313 (40 CFR 372). This information must be included in all MSDS's that are copied and distributed for this material.

Section 16: Other Information

This SDS was prepared in accordance with the new OSHA HCS requirements that will go into effect for manufacturers of chemicals on June 2015. This SDS replaces all preceding versions of MSDS and complies with all current regulations.

Revision: August 2023 - All rights reserved.

Disclaimer: The information contained in this SDS is based on data from sources considered to be reliable but Epoxy King does not guarantee the accuracy or completeness thereof. Epoxy King recommends that each customer or recipient of this SDS studies it carefully to become knowledgeable of and understand the risk and hazards associated with this product. The reader should consider consulting individuals who are experts in ventilation, toxicology or fire and understand the data in this SDS.



SC110 SDS - Hardener